



Technical Data		Cable Structure	
Core temperature, max.	70°C in Operation	Conductor	Solid Copper Conductor Class 1
Max. Short Circuit Temperature	160°C / 5 sec.	Insulation	PVC
Rated Voltage	450 / 750 V	Color of Insulation	Black
Bending Radius, min.	12xD	Sheath	No Sheath

Application

RE - Stranded copper conductor

H07V -U is a Single core cable with solid copper conductor and is with PVC insulation. It is used in the connections of mobile devices, in closed and dry places inside the building, under or above the plaster, where there is little mechanical stress. Nominal voltage 450/750 V.

DIMENSIONS AND WEIGHTS				ELECTRICAL PROPERTIES		
Number of cores x Nominal Cross Section	Conductor Shape	Outer Diameter of Cable (Approximately)	Weight of Cable (Approximately)	Length of Cable (Approximately)	Conductor DC Resistance at 20 °C	Rated current carrying capacity (A)
No x mm²						In Air 30 °C
1x1,5	RE	2,8	20	100	12,1	24
1x2,5	RE	3,3	31	100	7,41	32
1x4	RE	3,8	46	100	4,61	42
1x6	RE	4,3	65	100	3,08	54
1x10	RE	5,5	108	100	1,83	73